

HILLSBORO ELEMENTARY SCHOOLS215 S.E. 6th Ave.
HILLSBORO, OR 97123MATERIAL SAFETY DATA SHEET CM 0121

MANUFACTURER: Beecham Home Improv. Prod. EMERGENCY TELEPHONE NO:
P.O. Box 277 (513)253-7154
Dayton, Ohio 45401 1-(800)-424-9300

SECTION I. MATERIAL IDENTIFICATION

Common/Trade Name: Weldwood Waterproof Cement
Chemical Name: N/A
Chemical Family: Adhesive

SECTION II. HAZARDOUS INGREDIENTS

Ingredients:	%	TLV Units
Mineral Spirits	N/A	300

SECTION III. PHYSICAL DATA

Boiling Point (*F):	212 deg F	Specific Gravity (Water=1):	1.18
Vapor Pressure (mm Hg):	3.0 @ 20deg C	Percent Volatile (By volume):	58.1
Vapor Density (Air=1):	4.7		
Solubility in Water:	Completely miscible	Evaporation Rate (Bu.Ac. = 1):	1.0
Appearance and Odor:	Beige mastic, slight solvent odor.		

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

Flash Point: None Flammable Limits: LEL 1.0 UEL 6.0
Extinguishing Media: Foam, Carbon Dioxide, dry chemicals
Special Fire Fighting Procedures: Self-contained breathing apparatus is recommended to protect from combustion products. Cool exposed containers with water.
Unusual Fire and Explosion Hazards: Containers may explode if exposed to extreme heat; isolate from heat, electrical equipment, sparks and open flames. Do not put in contact with oxidizing materials.

SECTION V. HEALTH HAZARD DATA

Threshold Limit Value: See Section II above
Effects of Overexposure: Inhalation of solvent vapor may cause irritation of the respiratory tract, by headache, dizziness, or possible unconsciousness. Prolonged skin exposure can cause drying of skin. If ingested causes vomiting, diarrhea, depressed respiration.

Eyes: N/A

Skin: See above information

Breathing: See information above.
Swallowing: See information above.
Emergency and First Aid Procedures:
Eyes: Flush with large amounts of water for 15 min. Contact a Physician.
Skin: Wash with soap and water. Consult a physician if irritation dev.
Breathing: Remove to fresh air; restore breathing if necessary. Contact a physician.
Swallowing: Do NOT induce vomiting. If victim is conscious, give water or milk. Contact a physician immediately.

SECTION VI. REACTIVITY DATA

Stability: Stable
Conditions To Avoid: Excessive heat
Incompatible With: Strong oxidizers and caustics
Hazardous Decomposition Products: Normal combustion products, i.e. COx, NOx
Hazardous Polymerization: Will not occur
Conditions To Avoid: None

SECTION VII. SPILL OR LEAK PROCEDURES

Procedures In Case of Spill or Leak: Use absorbent material or scrape up dried material and place into containers. Large spills- Eliminate all sources of ignition and provide ventilation in spill area. Contain spill by diking to prevent spreading. Absorb spill with sand, earth, oil dry or other absorbent material and shovel into containers. Prevent run-off to sewers, streams, lakes or other bodies of water; notify local health and wildlife officials if run-off occurs.

SECTION VIII. SPECIAL PROTECTION INFORMATION

Type of Respiratory Protection: NIOSH/MSHA respirator(8-hr exposure limit)
Ventilation: Provide sufficient mechanical ventilation to maintain adequate air movement to keep exposure below limits and values.
Protective Gloves: Recommended for prolonged or repeated contact w/skin.
Waste Disposal: Discard spill residue may be incinerated. Dispose accord. to Fed., State, and local regulations. Liquids CANNOT be disposed of in a landfill.
Eye Protection: Provide eyewash if eye contact with product may occur.
Other Protective Equipment: N/A

SECTION IX. SPECIAL PRECAUTIONS

Handling/Storage Precautions: Keep containers from excessive heat & freezing. Keep containers tightly closed when not in use. Keep out of reach of children.
Other Precautions: Harmful or fatal if swallowed. Use only with adequate ventilation and eliminate sources of ignition when product is used. Avoid prolonged or repeated breathing of vapors & skin contact. Remove clothing & wash before reuse.

Date of Preparation: August 1, 1985