



## HILLSBORO ELEMENTARY SCHOOLS

215 S.E. 6th Ave.  
HILLSBORO, OR 97123

MATERIAL SAFETY DATA SHEET CM 0018

## SECTION I

PRODUCT CODE NUMBER: \_\_\_\_\_ \*TLV \_\_\_\_\_  
MANUFACTURER'S NAME: Alco Products, Inc. EMERGENCY INFORMATION (818) 764-7700  
MANUFACTURER'S ADDRESS 13126 Saticoy Street, North Hollywood, CA 91605  
PRODUCT: ANN-NEW Acoustical Tile Whitener COMMON NAME: \_\_\_\_\_  
GENERIC NAME: \_\_\_\_\_ CHEMICAL NAME: \_\_\_\_\_  
CHEMICAL FAMILY: \_\_\_\_\_ DOT PROPER SHIPPING NAME: \_\_\_\_\_  
WARNING STATEMENTS: \_\_\_\_\_

## SECTION II - INGREDIENTS

| Hazardous Mixtures of other Liquids, Solids, or Gases: | %    | TLV     |
|--------------------------------------------------------|------|---------|
| Aromatic Hydrocarbon Solvents                          | 9.8  | 200 ppm |
| Aliphatic Hydrocarbon solvent                          | 3.2  | 150 ppm |
| Methylene Chloride                                     | 23.0 | 300 ppm |
| 1,1,1-Trichloroethane                                  | 5.0  | 350 ppm |
| Isobutane-Propane Propellant                           | 25.0 | N/A     |
| Ketones                                                | 11.0 | 200 ppm |

\* Threshold limit value set by (A) OSHA, (B) ACGIH, (C) See Section III, (D) Other, (NE) Not Established (Units are in PPM unless otherwise specified)

## SECTION III - PHYSICAL DATA

APPROXIMATE BOILING RANGE: \_\_\_\_\_ VAPOR PRESSURE: \_\_\_\_\_  
VAPOR DENSITY: Heavier. SOLUBILITY IN WATER: \_\_\_\_\_  
SPECIFIC GRAVITY: 10.15 PERCENT VOLATILE by volume: 80%  
EVAPORATION RATE: Slower than ether. APPROXIMATE BULK DENSITY: \_\_\_\_\_

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT RANGE: Less than 20°F EXTINGUISHING MEDIA: Foam, Carbon Dioxide, Dry Chemical  
FIRE FIGHTING PROCEDURES: Keep cool with water spray. OOT FLAMMIBILITY CLASSIFICATION: \_\_\_\_\_  
Remove from fire area. In common with all pressurized products, should not be stored  
UNUSUAL FIRE AND EXPLOSION HAZARDS: near heat, sparks, or open flame, store at temperatures below 120°F. Do not

## SECTION V - EMERGENCY AND FIRST AID PROCEDURES

puncture or incinerate (Use in well ventilated area)  
EYE CONTACT: If spray gets in eyes, flush with large quantities of water. Take to a doctor.  
SKIN CONTACT: \_\_\_\_\_  
INHALATION: Remove from area.  
INGESTION: \_\_\_\_\_

## SECTION VI - PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

ACUTE EFFECTS See Section II. EFFECTS OF OVEREXPOSURE: Anesthetic.

CHRONIC EFFECTS \_\_\_\_\_

## SECTION VII - REACTIVITY DATA

STABILITY (Conditions to Avoid): Stable. Storage above 120°F.

INCOMPATIBILITY (Materials to Avoid): \_\_\_\_\_

HAZARDOUS DECOMPOSITION PRODUCTS: \_\_\_\_\_

HAZARDOUS POLYMERIZATION (Conditions to Avoid): \_\_\_\_\_

## SECTION VIII - SPILL OR LEAK PROCEDURES

PROCEDURES IN CASE OF RELEASE OR SPILL: N/AWASTE DISPOSAL METHOD: Empty or full containers should not be punctured nor incinerated.

## SECTION IX - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use in well ventilated area.

VENTILATION: \_\_\_\_\_

PROTECTIVE GLOVES: N/AEYE PROTECTION: N/AOTHER PROTECTIVE EQUIPMENT: N/A

## SECTION X - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORING PRECAUTIONS Do not store above 120°F. Do not puncture nor incinerate.

OTHER PRECAUTIONS: \_\_\_\_\_

## SECTION XI - DOCUMENTARY INFORMATION

PRODUCT CODE NUMBER: \_\_\_\_\_

ISSUE DATE: \_\_\_\_\_

REPLACES MSDS NUMBER: \_\_\_\_\_

PREVIOUS PRODUCT CODE NUMBER: \_\_\_\_\_

PREVIOUSLY ISSUED: \_\_\_\_\_