



MATERIAL SAFETY DATA SHEET

Consumer Products Division, Division of Borden, Inc.
180 EAST BROAD STREET, COLUMBUS, OHIO 43215

Emergency Telephone
(614) 431-6600
(OPERATION ALERT)

2020

PNT177

THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 REQUIRES THAT
: INFORMATION CONTAINED ON THIS SHEET BE MADE AVAILABLE TO YOUR WORKERS
INSTRUCT YOUR WORKERS TO HANDLE THIS PRODUCT PROPERLY

NAME KRYLDN INT./EXT. ENAMEL OR ENGINE COLOR
TYPE SPRAY PAINT "AERDSOL"
APPLICATION: ITEM NOS.: 1501 THRU 2505 — 1501 GLOSSY WHITE; 1502 FLAT WHITE; 1503 ANTIQUE WHITE; 1506 ALMOND; 1601 GLOSSY BLACK; 1602 ULTRA FLAT BLACK; 1603 CHARCOAL GRAY; 1604 SHADDW GRAY; 1605 DOVE GRAY; 1608 SMOKE GRAY; 1611 UNIVERSAL GRAY, ENGINE COLOR; 1612 UNIVERSAL BLACK, ENGINE COLOR; 1613 SEMI-FLAT BLACK; 1617 PEARL GRAY; 1619 CAST MAGIC; 1631 BLACK LACQUER; 1704 SPANISH BROWN; 1705 ENGINE GOLD, ENGINE COLOR; 1801 CHROME YELLOW; 1802 PASTEL YELLOW; 1803 MARIGOLD YELLOW (OLD CATERPILLAR YELLOW); 1804 BRIGHT YELLOW (JOHN DEERE YELLOW); 1809 SCHOOL BUS YELLOW; 1811 HARVEST GOLD; 1813 DAISY YELLOW (OSHA SAFETY YELLOW); 1814 TOPAZ YELLOW (NEW CATERPILLAR YELLOW); 1901 REGAL BLUE; 1902 BABY BLUE; 1903 METALLIC BLUE; 1908 CHEVRDLET BLUE, ENGINE COLOR; 1909 FORD BLUE, ENGINE COLOR; 1910 TRUE BLUE; 1923 FORD DARK BLUE, ENGINE COLOR; 1928 CHRYSLER LIGHT BLUE, ENGINE COLOR; 1929 PLUM (SAFETY PURPLE); 1930 G.M. BLUE, ENGINE COLOR; 2001 HUNTER GREEN; 2002 PASTEL AQUA; 2004 MOSS GREEN (JOHN DEERE/CASE GREEN); 2005 ERIN GREEN (OLIVER GREEN; 2007 FORD GREEN, ENGINE COLOR; 2008 AQUA TURQUOISE; 2009 AVOCADD; 2011 JUNGLE GREEN; 2012 CLOVER GREEN (SAFETY GREEN); 2013 G.M. ALPINE GREEN (DETROIT DIESEL), ENGINE COLOR; 2101 CHERRY RED; 2103 AMERICAN BEAUTY RED (INTERNATIONAL HARVESTER RED); 2106 FORD RED, ENGINE COLOR; 2108 BANNER RED; 2110 HOT PINK; 2111 CHRYSLER RED, ENGINE COLOR; 2114 BUICK RED, ENGINE COLOR; 2116 SCARLET (OSHA SAFETY RED); 2117 BDNFIRE; 2118 BURGUNDY; 2301 O.D. KHAKI; 2401 SUNSET DRANGE; 2404 MANDARIN DRANGE; 2405 CHEVRDLET ORANGE, ENGINE COLOR; 2406 BURNT ORANGE; 2410 POPSICLE ORANGE (SAFETY ORANGE); 2411 BRICK; 2501 LEATHER BROWN; 2504 BEIGE, 2505 CHIPPEWA; 15012 GLOSSY WHITE; 15022 FLAT WHITE; 15032 ANTIQUE WHITE; 15062 ALMOND; 16012 GLDSSY BLACK; 16022 ULTRA FLAT BLACK; 16052 DOVE GRAY; 16082 SMDKE GRAY; 16132 SEMI FLAT BLACK; 18042 BRIGHT YELLOW; 19012 REGAL BLUE; 20012 HUNTER GREEN; 21012 CHERRY RED; 21082 BANNER RED; 25012 LEATHER BROWN; 25042 BEIGE

30-June-86

SIGNAL WORD- DANGER!

THIS MATERIAL IS A "HEALTH HAZARD" AND/OR A "PHYSICAL HAZARD" AS DETERMINED WHEN REVIEWED ACCORDING TO THE REQUIREMENTS OF THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION 29 CFR PART 1910.1200 "HAZARD COMMUNICATION" STANDARD.

CHEMICAL HAZARD RATING

HEALTH=2(MODERATE)

FIRE=4(EXTREME)

REACTIVITY=0(LEAST)

CHRONIC=*

29CFR1910.1200 HAZARDOUS INGREDIENTS/REPORTED HEALTH EFFECTS

CAS REGISTRY NO.	MATERIAL DESCRIPTION	% BY WT.
67-64-1	ACETONE	36-37.
CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION. ACGIH TLV: 750 PPM (1780 MG/M3) TWA; 1000 PPM(2375 MG/M3) STEL OSHA PEL: 1000 PPM (2400 MG/M3) TWA NIOSH DOCUMENT NUMBER: 78-173		
71-36-3	BUTYL ALCOHOL	0.2-2.5
CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION. ACGIH TLV: SKIN - 50 PPM (50 MG/M3) CEILING OSHA PEL: 100 PPM (300 MG/M3) TWA		
74-98-6	PROPANE	16-17.
THIS MATERIAL IS A SIMPLE ASPHYXIANT. SIGNS AND SYMPTOMS OF OVEREXPOSURE INCLUDE CYANOSIS, RESPIRATORY DISTRESS, HEADACHE, DIZZINESS, DROWSINESS, UNCONSCIOUSNESS AND ASPHYXIATION. CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. ACGIH TLV: SIMPLE ASPHYXIANT-SEE ACGIH TLVS. APPENDIX E OSHA PEL: 1000 PPM (1800 MG/M3) TWA		
78-93-3	METHYL ETHYL KETONE	8-17.
POSSIBLE REPRODUCTIVE HAZARD. OVEREXPOSURE MAY CAUSE FEMALE REPRODUCTIVE DISORDERS BASED ON TEST WITH LABORATORY ANIMALS CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS, AND EVEN ASPHYXIATION. ACGIH TLV: 200 PPM (590 MG/M3) TWA; 300 (885 MG/M3) STEL OSHA PEL: 200 PPM (590 MG/M3) TWA NIOSH DOCUMENT NUMBER: 78-173		

108-10-1 METHYL ISOBUTYL KETONE 2-4
CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION. ACGIH TLV: 50 PPM (205 MG/M3) TWA; 75 PPM (300 MG/M3) STEL OSHA PEL: 100 PPM (410 MG/M3) TWA NIOSH DOCUMENT NUMBER: 78-173

108-65-6 2-PROPANOL, 1-METHOXY-, ACETATE 7-0

108-88-3 TOLUENE 2-3
OVEREXPOSURE MAY CAUSE LIVER DAMAGE. OVEREXPOSURE MAY CAUSE KIDNEY DAMAGE. CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS ASPHYXIATION. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY LEAD TO ADDICTION AND MAY BE HARMFUL OR FATAL. ACGIH TLV: 100 PPM (375 MG/M3) TWA, 150 PPM (560 MG/M3) STEL OSHA PEL: 200 PPM TWA, 300 PPM CEILING; 500 PPM 10-MIN. PEAK NIOSH DOCUMENT NUMBER: 73-11023

1330-20-7 XYLENE 6-14
OVEREXPOSURE MAY CAUSE LIVER DAMAGE. OVEREXPOSURE MAY CAUSE KIDNEY DAMAGE. CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION. ACGIH TLV: 100 PPM (435 MG/M3) TWA; 150 PPM (655 MG/M3) STEL OSHA PEL: 100 PPM (435 MG/M3) TWA NIOSH DOCUMENT NUMBER: 75-168
SEE REVERSE SIDE

PHYSICAL DATA

VAPOR PRESSURE -- SEE CAN PRESSURE
VAPOR DENSITY HEAVIER THAN AIR
SOLUBILITY IN WATER -- SLIGHT
SPECIFIC GRAVITY LIGHTER THAN WATER
EVAP RATE FASTER THAN BUTYL ACETATE
BOILING POINT; APPEARANCE; ODDR -- N.A.
PERCENT VOLATILE BY WEIGHT 81 TO 89
PERCENT NON-VOLATILE BY WEIGHT 11 TO 19
PRESSURE IN CONTAINER, PSIG @ 70 F. APPROX. 60

ACUTE HEALTH HAZARD DATA

SKIN ABSORPTION: NOT EXPECTED TO BE HARMFUL UNDER NORMAL CONDITIONS OF USE.
INGESTION: MAY BE HARMFUL IF SWALLOWED.
INHALATION: MAY BE HARMFUL IF INHALED. LIQUID OR VAPOR CAN CAUSE IRRITATION OF NOSE, THROAT AND LUNGS.
SKIN: CAUSES IRRITATION.
EYES: CAUSES IRRITATION.

HANDLING PRECAUTIONS

SKIN ABSORPTION: AVOID PROLONGED OR REPEATED CONTACT WITH EYES, SKIN OR CLOTHING.
INHALATION: AVOID BREATHING VAPOR OR MIST. USE WITH ADEQUATE VENTILATION.
SKIN: AVOID CONTACT WITH SKIN.
EYES: AVOID CONTACT WITH EYES.
HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES. THESE PRACTICES INCLUDE AVOIDING UNNECESSARY EXPOSURE AND REMOVAL OF THE MATERIAL FROM EYES, SKIN AND CLOTHING.
WASH THOROUGHLY AFTER HANDLING.

EMERGENCY AND FIRST AID PROCEDURES

INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.
SKIN ABSORPTION: IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES OR SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.
INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN.
SKIN CONTACT: FLUSH SKIN WITH WATER. IF IRRITATION PERSISTS, CALL A PHYSICIAN.
EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. EYELIDS SHOULD BE HELD APART DURING IRRIGATION TO INSURE WATER CONTACT WITH ENTIRE SURFACE OF EYES AND LIDS. CALL A PHYSICIAN.

FIRE AND EXPLOSION HAZARD DATA

EXTREMELY FLAMMABLE.
CONTENTS UNDER PRESSURE; EXPOSURE TO HIGH TEMPERATURE MAY CAUSE BURSTING. AVOID RADIATORS, STOVES, DIRECT SUNLIGHT, OR OTHER HEAT SOURCE. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT SPRAY NEAR OPEN FLAME.
IN CASE OF FIRE, USE DRY CHEMICAL, FOAM OR CO2. WATER MAY BE INEFFECTIVE, BUT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL.

REACTIVITY DATA

NORMALLY STABLE AS DEFINED IN NFPA 704-12(4-3.1).
MAJOR DECOMPOSITION PRODUCTS: CO, CO2
HAZARDOUS POLYMERIZATION WILL NOT OCCUR

CONTROL MEASURES

IF AIRBORNE CONTAMINANTS ARE GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, SUFFICIENT VENTILATION IN VOLUME AND AIR FLOW PATTERNS SHOULD BE PROVIDED TO KEEP AIR CONTAMINANT CONCENTRATION LEVELS BELOW ACCEPTABLE CRITERIA.

ENGINEERING CONTROLS: THE FOLLOWING EXPOSURE CONTROL TECHNIQUES MAY BE USED TO EFFECTIVELY MINIMIZE EMPLOYEE EXPOSURE: LOCAL EXHAUST VENTILATION, ENCLOSED SYSTEM DESIGN, PROCESS ISOLATION AND REMOTE CONTROL IN COMBINATION WITH APPROPRIATE USE OF PERSONAL PROTECTIVE EQUIPMENT AND PRUDENT WORK PRACTICES. THESE TECHNIQUES MAY NOT NECESSARILY ADDRESS ALL ISSUES PERTAINING TO YOUR OPERATIONS. WE, THEREFORE, RECOMMEND THAT YOU CONSULT WITH EXPERTS OF YOUR CHOICE TO DETERMINE WHETHER OR NOT YOUR PROGRAMS ARE ADEQUATE.

PERSONAL PROTECTION INFORMATION

WHERE AIR CONTAMINANTS CAN EXCEED ACCEPTABLE CRITERIA, USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION EQUIPMENT. RESPIRATORS SHOULD BE SELECTED BASED ON THE FORM AND CONCENTRATION OF CONTAMINANTS IN AIR IN ACCORDANCE WITH OSHA 29 CFR 1910.134 OR OTHER APPLICABLE STANDARDS OR GUIDELINES.
USE GOGGLES IF CONTACT IS LIKELY.
WEAR IMPERVIOUS GLOVES AS REQUIRED TO PREVENT SKIN CONTACT. *

SPILL OR LEAK PROCEDURES

ELIMINATE ALL IGNITION SOURCES.
SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL AREA.
PREVENT ENTRY INTO NATURAL BODIES OF WATER.

WASTE DISPOSAL METHOD

DISPOSE OF ACCORDING TO LOCAL, STATE, AND FEDERAL REQUIREMENTS.
EMPTY CONTAINER: MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEARBY. INCINERATION WILL CAUSE CONTAINER TO BURST VIOLENTLY.

STORAGE PRECAUTIONS

DO NOT STORE AT TEMPERATURES OVER 120 F.

DOT CLASSIFICATION

ORM-D CONSUMER COMMODITY

NOR(M) KD-1501C 06/30/86

DISCLAIMER

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY BORDEN, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States patent. The information provided herein was believed by Borden to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.