## HILLSBORO ELEMENTARY SCHOOLS

MATERIAL SAFETY DATA SHEET

CM 0126



215 E.E. SIB Ave. HILLSBORD, OR 97123

TOFNT TETCATTON

PRODUCT NAME OR NUMBER (as it appears on label) XTRACTION II

WANLFACTURER'S NAME

Spartan Chemical Co., Inc.

EMERGENCY TELEPHONE NO.

(419) 531-5551

ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE)

110 N. Westwood Ave., Toledo, OH 43607

HANUFACTURER'S D-U-N-S NO.

00-503-6728

SECTION II  HAZARDOUS INGREDIENTS						
  CAS REGISTRY NO.	1 ] XX   ]	CHENTICAL NAME(S)			Ceiling	CARCINOGEN     CARCINOGEN
*111-76-2	2	2-Butoxyethanol	120	-	-	na

<sup>\*</sup>This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (SARA) and of 40 CRF 372.

	·	ION III CAL DATA				i
BOILING POINT	SPECIFIC GRAVITY			, · · · · · · · · · · · · · · · · · · ·		
212 °F0	C 1.049 _	_				
VAPOR PRESSURE - 18	•	• •	PERCENT SI	OLID BY	•	
8 75 °F °C _x mm Hg	psi		WEIGHT (%)	)		
VAPOR DENSITY (AIR = 1) Unknown	EVAPORATION RATE :	(but. ace. = 1)	9-11			
SOLUBILITY IN WATER	APPEARANCE AND OD	no				
Complete	Clear, light gree					
pH	floral fragrance	-	IS HATERIA	¥.:	(LIQUID)	SOLI
11.3-11.8	, <b>.</b>		GAS	PASTE		-
	SECT	ION IV	<del></del>	<del></del>		
	FIRE AND EXPLOS	ION HAZARO DATA				<u>. 1</u>
FLASH POINT	METHOD USED - ASTM - D92	FLANNABLE LINITS				
None	-	.n/a <sub>t ,</sub>				
EXTINGUISHING MEDIA	• •	• •			<u>.</u>	•
n/a					•	

None

UNUSUAL FIRE AND EXPLOSION HAZAROS None

	on v - Health Hazaro		1
EFFECTS OF OVEREXPOSURE - CONDITIONS TO AVOID		MIT VALUE - Not established	
Dryness of skin with prolonged contact; dizzin	ess with excessive b	reathing of vapors. Avoid	٨
eye contact; may cause eye irritation. Butoxy	ethanol is absorbed	through the skin which may	•
affect the liver, kidneys, lymph and blood sys	tems; inhalation may	irritate throat and	
respiratory system.			
PRIMARY ROUTES OF ENTRY INHALATION X	SKIN CONTACT <u>x</u>	OTHER (SPECIFY)	
CONDITIONS ACCRAVATED BY USE - Unknown			
EMERGENCY AND FIRST ALD PROCEDURES - In case o	f contact immediately	v flush evec with alanty of	
water for at least 15 minutes; call a physicia	n. Flush skin with	water. If swallowed, give	
large quantities of water or fruit juice. Cal	l a physician immedia	ately.	
		<u> </u>	
	ON VI - REACTIVITY D	ATA	
STABILITY: UNSTABLE STABLE ×			_
INCOMPATIBILITY (MATERIALS TO AVOID)			
Strong oxidizing agents			
HAZARDOUS DECOMPOSITION PRODUCTS			
None known			
HAZARDOUS MAY OCCUR			
POLYMERIZATION: WILL NOT OCCUR X			
SECTION VI	I - SPILL OR LEAK PRO	CEDURES	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED			
Flush through normal sanitary sewer system with	large amounts of wa	ter.	16
			()
NASTE DISPOSAL METHOD			
Same as above.			•
SECTION VIII -	SPECIAL PROTECTION	ONFORMATION	<sub>I</sub>
RESPIRATORY PROTECTION (SPECIFY TYPE)			<del></del> -
None			
VENTILATION - Good general ventilation should b		conditions. Local	
exhaust ventilation may be necessary for some o	Derations.		
PROTECTIVE GLOVES (SPECIFY TYPE)	EVE PROTECTION	(SPECIFY TYPE)	•
Solvent resistant	Safety glasses		
	, <b>91</b> 0000		
OTHER PROTECTIVE EQUIPMENT			
None necessary			
	· <u>-</u> -		
·	IX - SPECIAL PRECAUT	IONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING			
Keep from freezing.			
OTHER PRECAUTIONS - None			
Spartan Chemical Co., Inc.	NAME TI	homas J. Mitchell	
XTRACTION II	TITLE 0.	irector of Research	1 6
Ref: 29 CFR 1910:1200 (OSHA)	DATE 3	une 1, 1990	1 3
		arch 7, 1989	- Jan C